

JTDX

The screenshot displays the JTDX software interface, which is used for digital voice communication. The main window is titled "JTDX - Wide Graph" and shows a frequency spectrum from 500 to 2500 kHz. Below the graph, the "JTDX by HF community" window is active, showing a list of received messages and various control panels.

Message List:

UTC	dB	DT	Freq	Message	Band Activity
22.02.19	06:14:29	UTC			30m
061415	-6	-0.3	2000	~ UA0ZC SP5XSD RR73	Poland
061415	-1	0.2	1375	~ V31YN SV1AVD -22	Greece
061415	-13	0.9	609	~ CQ UA3PAB KO84	EU Russ
061415	-11	0.1	1769	~ HB9EUW OH3OJ -07	Finland
061415	-9	0.3	1866	~ CQ 4X5MZ KM71	Israel

Control Panels:

- Frequency:** 10.136 000
- Time:** 06:14:35
- TX:** TX 00/30
- Power:** 30m
- Message:** CQ EA3FAJ JN11
- Response:** TNX 73
- Buttons:** Enable Tx, Halt Tx, Log QSO, Hint, AGCc, Decode, Clear DX, CQ, RRR, AnsCQ, SkpGrid, Grid, dB, R+dB, RR73, 73, Gen msg, Free msg.

Bottom Panel:

SP5XSD	SV1AVD	UA3PAB	OH3OJ	4X5MZ
Poland	Greece	Russia (EU)	Finland	Israel